



# Trenchguard

## Edge Protection System for Trenching & Shoring

**Trenchguard** has been designed to protect work personnel from open excavations & falling debris.

**Trenchguard** conforms to the latest temporary edge protection standard BS EN 13374.

**Trenchguard** has a built in toe board to prevent debris from falling onto operatives working below.

**Trenchguard** is lightweight for ease of use by site operatives & is quick to install when used in conjunction with post and sheeppile clamp & trenchbox clamp.



**Rapid Panel** (see above) = 2245mm wide x 1150mm high

Clamp is adjustable with a speed thread.

Clamp is suitable for use with trench sheets from 6mm to 30mm thickness & trench boxes up to 120mm.

Clamp is produced by the leading manufacturers. Designed to be used in conjunction with post and

### **Trenchguard**

Fits boxes from 45mm to 120mm

Fits sheets from 6mm to 30mm

### **Post**

Galv. Steel Tube 48.3mm o/d x 4mm wall x 1200mm long - Complete with plastic end cap



**Cost Effective Quick & Easy Installation**

**COMPETITIVE PRICES & DISCOUNTS AVAILABLE**

**Tel: (+44)161 633 0425**

**Email: [info@alliedscaffolding.co.uk](mailto:info@alliedscaffolding.co.uk)**

**[www.alliedscaffolding.co.uk](http://www.alliedscaffolding.co.uk)**